



LIGHTING OUTPUT

CONSTANT & STROBE & TRIGGER:
 CH1-4: 5V / 1000mA / 5W
 CH1-4: 12V / 1000mA / 12W
 CH1-4: 24V / 1000mA / 24W
 CH1-4: 48V / 1000mA / 48W
 *per channel

ONE TO ONE / LOOP

* IF LIGHTING INPUT POWER
 SAME AS CONTROLLER INPUT POWER,
 IT CAN LOOP WITH SAME
 POWER SUPPLY

**CONTROLLER
 INPUT POWER**
 12V / 24V

CONTROLLER
 INPUT
OPTIONAL
 * ONLY INPUT 1
 WORKS

CONTROLLER
 OUTPUT
OPTIONAL
 * ONLY OUTPUT 1
 WORKS

LC-16-4CH-SQ

DESIGN BY	DANIEL	UNIT: MM
CHECK BY	NIZAM	SIZE A4
DATE	26/11/2024	SCALE: 1 : 1
MATERIAL	-	REVISION: 01
FINISHING	-	WEIGHT: -
QTY	-	-

PRODUCT SERIES: LC-16 SERIES		
TITLE	DRAWING LAYOUT	GEN. TOLERANCES
PART NO	-	X ±0.15
DWG NO	LC-16-4CH-SQ	X.X ±0.1
		X.XX ±0.05
		SHEET 1 OF 1

