Extension Wire

NO	Name	TMS PART NUMBER	BASLER PART NUMBER	IMAGES	INPUT	OUTPUT	DESCRIPTION	CABLE LENGTH	PIN ASSIGNMENT (INPUT & OUTPUT)	CABLE INFORMATION	DRAWING LAYOUT	WEBSITE LINK	Packaging
1	M12 FEMALE CABLE WITH FLYING LEAD (3M)	BA-EXT-FL-M12F-3M-24V		Ó	M12 Connector (Female)	open end for terminal block	Female moled with cable, Unshielded, metal screw, solder	3m		AWG 2*24AWG Current Rating 3A Voltage Rating 300V		<u>EXT-FL-M12F-3M-</u> <u>24V</u>	Θ
2	M12 FEMALE CABLE WITH FLYING LEAD (SM)	BA-EXT-FL-M12F-SM-24V		Ó	M12 Connector (Femsle)	GND 24V	Female moled with cable, Unshielded, metal screw, solder	Sm		AWG 2*24AWG Current Rating 3A Voltage Rating 300V		NA	C
3	M12 FEMALE CABLE WITH SM CONNECTOR (3M)	BA-EXT-SM-M12F-3M-24V		ð.	M12 Connector (Fermale)	to JST -3 PIN	Female moled with cable, Unshielded, metal screw, solder	3m		AWG 2*24AWG Current Rating 3A Voltage Rating 300V	The second secon	<u>EXT-SM-M12F-3M-</u> <u>24V</u>	0
4	M12 FEMALE CABLE WITH SM CONNECTOR (SM)	BA-EXT-SM-M12F-SM-24V		ĺΟ,	M12 Connector (Female)	to JST -3 PIN	Female moled with cable, Unshielded, metal screw, solder	5m		AWG 2*24AWG Current Rating 3A Voltage Rating 300V	An Andrew Constraints	NA	0
5	M12 FEMALE CABLE WITH 4x SM CONNECTOR (3M)	BA-EXT-4CH-M12F-3M-24V			M12 Connector (Female)	to 4-Channel	Female moled with cable, Unshielded, metal screw, solder	3m		AWG 2*24AWG Current Rating 3A Voltage Rating 300V		NA	0
6	M12 FEMALE CABLE WITH 4x RGBW CONNECTOR (3M)	BA-EXT-RGBW-M12F-3M-24V			M12 Connector (Female)	to RGBW (4-Channel)	Female moled with cable, Unshielded, metal screw, solder	3m		AWG 2*24AWG Current Rating 3A Voltage Rating 300V		EXT-RGBW-M12F- <u>3M-24V</u>	Q