







Extension wire

Name	TMS PART NUMBER	BASLER PART NUMBER	IMAGES	INPUT	OUTPUT	DESCRIPTION	CABLE LENGTH	PIN ASSIGNMENT (INPUT & OUTPUT)	CABLE INFORMATION		DRAWING LAYOUT	WEBSITE LINK	Packaging																								
M12 FEMALE CABLE WITH FLYING LEAD (5M)	BA-EXT-FL-M12F-5M-24V			M12 Connector (Female) 	open end for terminal block 	Female moled with cable, Unshielded, metal screw, solder	5m	<div><div>FEMALE</div><table><tr><td>PIN 1</td><td>BROWN</td><td>24V</td></tr><tr><td>PIN 2</td><td>WHITE</td><td>-</td></tr><tr><td>PIN 3</td><td>BLUE</td><td>GND</td></tr><tr><td>PIN 4</td><td>BLACK</td><td>-</td></tr><tr><td>PIN 5</td><td>GRAY</td><td>-</td></tr></table><div><table><tr><td>PIN 1</td><td>BROWN (+VE)</td></tr><tr><td>PIN 2</td><td>BLUE (-VE)</td></tr></table></div></div>	PIN 1	BROWN	24V	PIN 2	WHITE	-	PIN 3	BLUE	GND	PIN 4	BLACK	-	PIN 5	GRAY	-	PIN 1	BROWN (+VE)	PIN 2	BLUE (-VE)	<table><tr><td>AWG</td><td>2*24AWG</td></tr><tr><td>Current Rating</td><td>3A</td></tr><tr><td>Voltage Rating</td><td>300V</td></tr></table>	AWG	2*24AWG	Current Rating	3A	Voltage Rating	300V		NA	
PIN 1	BROWN	24V																																			
PIN 2	WHITE	-																																			
PIN 3	BLUE	GND																																			
PIN 4	BLACK	-																																			
PIN 5	GRAY	-																																			
PIN 1	BROWN (+VE)																																				
PIN 2	BLUE (-VE)																																				
AWG	2*24AWG																																				
Current Rating	3A																																				
Voltage Rating	300V																																				